


PLAN — FLAT DRIVEWAY
(≤5%)

GENERAL NOTES:

1. REFER TO THE 2017 CITY OF EDMONDS STORMWATER ADDENDUM FOR SETBACK AND INFEASIBILITY REQUIREMENTS.
2. SEE EDMONDS CITY CODE AND COMMUNITY DEVELOPMENT CODE SECTION 18.80.070 FOR DRIVEWAY DESIGN REQUIREMENTS.
3. SHEET FLOW DISPERSION MAY BE USED FOR OTHER SURFACES, INCLUDING BUT NOT LIMITED TO, PATIOS, SPORT COURTS, LAWNS, PASTURES, OR OTHER SURFACES WHERE FLOWS ARE NOT CONCENTRATED.

NOTES:

1. TRANSITION ZONE SHALL BE A 2 FOOT WIDE BY 6 INCH THICK GRAVEL TRENCH CONFORMING TO REQUIREMENTS OF WSDOT SPEC. 9-03.12(5), GRAVEL BACKFILL FOR DRYWELLS.
2. A VEGETATED BUFFER MUST BE PROVIDED IN ACCORDANCE THE 2017 CITY OF EDMONDS STORMWATER ADDENDUM REQUIREMENTS.
3. WIDTH OF VEGETATED BUFFER SHALL BE 10 FEET (MIN) FOR DRIVEWAY WIDTH UP TO 20 FEET AND 20' (MIN) FOR DRIVEWAY WIDTH UP TO 40' OF IMPERVIOUS SURFACE. VEGETATED BUFFER SHALL BE MEASURED PERPENDICULAR TO SITE CONTOURS.



CITY OF EDMONDS
PUBLIC WORKS
DEPARTMENT

**TYPICAL SHEET
FLOW DISPERSION**

APPROVED BY: R. ENGLISH

REVISION DATE
APRIL 2021

STANDARD
DETAIL
SD-635